



Series 200 Monitor

Features

- High accuracy
- Rapid T90 response
- Ergonomic design
- Simple operation
- Large easy to read display
- Remote sensor capability
- Portable & wall mountable
- Interchangeable sensor heads
- Battery & AC mains power



Specifications

Base unit

Measurement units	ppm or mg/m ³
Reading functions	Minimum / Maximum / Average / ST-15
Interchangeable sensor head	Yes
Onboard alarm	No
Low battery indicator	Yes
Sensor condition indicator	Yes
Stand-by mode	Yes
Zero-cal function	Yes
Power supply	12 VDC, 800 mA - power adaptor supplied
Rechargeable long-life battery	Ni-MH 9.6 VDC; 2100 mA/h
Wall mountable	Yes - use R33 wall bracket
Remote sensor capability	Yes - use R10 or R13 remote kit
Durable enclosure	Yes - PC & ABS
Enclosure rating	IP20 & NEMA 1 equivalent
Dimensions (with sensor head)	195 x 122 x 54 (mm); 7 ⁵ / ₈ x 4 ³ / ₄ x 2 ¹ / ₈ (in)
Weight (with sensor head & battery)	< 460 g; < 16 oz
Approvals	Part 15 of FCC Rules EN 50082-1: 1997 EN 50081-1: 1992

